

PARKELL PRODUCTS -- SNAP/RELATE MONOMER S441 / 458M -- 6520-00F012299

=====
Product Identification
=====

Product ID:SNAP/RELATE MONOMER S441 / 458M
MSDS Date:07/31/1984
FSC:6520
NIIN:00F012299
MSDS Number: BJCDD
=== Responsible Party ===
Company Name:PARKELL PRODUCTS
Address:155 SCHMITT BLVD
Box:S
City:FARMINGDALE
State:NY
ZIP:11735
Info Phone Num:(516) 249-1134
Emergency Phone Num:(516) 249-1134
CAGE:FO568
=== Contractor Identification ===
Company Name:PARKELL
Address:155 SCHMITT BLVD
Box:376
City:FARMINGDALE
State:NY
ZIP:11735
Phone:(516) 249-1134
CAGE:24040
Company Name:PARKELL PRODUCTS INC (FORMERLY IN LONG ISLAND NY)
Address:155 SCHMITT BLVD
Box:376
City:FARMINGDALE
State:NY
ZIP:11735-1403
Country:US
Phone:800-535-5053/800-243-7446
CAGE:FO568

=====
Composition/Information on Ingredients
=====

Ingred Name:ALKYL METHACRYLATE
Fraction by Wt: >90%
ACGIH TLV:100 PPM

Ingred Name:ETHYLENE GLYCOL DIMETHACRYLATE
CAS:97-90-5
RTECS #:OZ4400000
Fraction by Wt: <5%

Ingred Name:N,N-DIMETHYL-P-TOLUIDINE, DIMETHYL-P-TOLUIDINE
CAS:99-97-8
RTECS #:XU5803000
Fraction by Wt: <5%

Ingred Name:4-METHOXYPHENOL
CAS:150-76-5
RTECS #:SL7700000
Fraction by Wt: 0.005%
OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LIQUID OR HIGH VAPOR CONCENTRATION CAN
IRRITATE EYES/RESPIRATORY SYSTEM. SKIN: CAUSE RASHES. INHALATION:
HEADACHES, NAUSEA, DROWSINESS & UNCONSCIOUSNESS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN: CAUSE RASHES. LIQUID OR HIGH VAPOR
CONCENTRATION CAN IRRITATE EYES/RESPIRATORY SYSTEM. INHALATION:
HEADACHE, NAUSEA, DROWSINESS & UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:RASHES

=====
First Aid Measures
=====

First Aid:INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, GIVE
ARTIFICIAL RESPIRATION. EYES: FLUSH W/WATER FOR 15 MIN. CALL
PHYSICIAN. SKIN: WASH W/SOAP & WATER. INGESTION: INDUCE VOMITING &
GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:44F
Extinguishing Media:CHEMICAL FOAM, CO2, DRY CHEMICALS
Fire Fighting Procedures:WEAR RESPIRATOR (PRESSURE-DEMAND),
SELF-CONTAINED BREATHING APPARATUS/FULL PROTECTIVE GEAR. USE WATER
SPRAY TO COOL CONTAINERS. FIGHT FIRE PROTECTED FROM AREAS.
Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL TO SOURCE OF
IGNITION/FLASH BACK. HEAT CAN CAUSE POLYMERIZATION W/RAPID RELEASE
OF ENERGY WHICH MAY RUPTURE CONTAINER EXPLOSIVELY.

=====
Accidental Release Measures
=====

Spill Release Procedures:EVACUATE AREA, ELIMINATE IGNITION SOURCES.
DIKE/ABSORB W/INERT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:GROUND ALL CONTAINERS WHEN
TRANSFERRING. USE EXPLOSION PROOF EQUIPMENT. CHECK INHIBITOR LEVEL
AFTER 3 MONTH.
Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WEAR RESPIRATOR (PRESSURE-DEMAND),
SELF-CONTAINED BREATHING APPARATUS, MSHA/NIOSH APPROVED OR
EQUIVALENT).
Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP 40F.
Hazardous Decomposition Products:CO, CO2
Conditions to Avoid Polymerization:SPONTANEOUS POLYMERIZATION MAY OCCUR
ON PROLONGED STORAGE WITH RELEASE OF ENERGY.

=====
Disposal Considerations
=====

Waste Disposal Methods:DON'T ALLOW TO DRAIN TO SEWER. INCINERATE LIQUID
IN PROPER EQUIPMENT. LANDFILL ABSORBED MATERIAL ACCORDING TO

REGULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.