

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Name:** HOLD™ LIQUID TRAY ADHESIVE

**Product Code:** 011460-000, 011462-000

### Intended Use of the Product

Designed to provide an improved retaining grip between the impression tray and any alginate and hydrocolloid impression material.

### Name, Address, and Telephone of the Responsible Party

#### **Company**

Water Pik, Inc.

1730 East Prospect Road

Fort Collins, CO 80553-0001

800/525-2020 (8 am- 4pm MST)

### Emergency Telephone Number

**Emergency Number** : 800/424-9300 (24 Hr: CHEMTREC)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Flam. Liq. 3 H226

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Repr. 2 H361

STOT SE 3 H336

STOT RE 2 H373

Asp. Tox. 1 H304

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**



#### **Signal Word (GHS-US)**

: Danger

#### **Hazard Statements (GHS-US)**

: H226 - Flammable liquid and vapor.  
 H304 - May be fatal if swallowed and enters airways.  
 H315 - Causes skin irritation.  
 H319 - Causes serious eye irritation.  
 H336 - May cause drowsiness or dizziness.  
 H361 - Suspected of damaging fertility or the unborn child.  
 H373 - May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary Statements (GHS-US)**

: P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from sparks, open flames, heat, hot surfaces. - No smoking.  
 P233+P235 - Keep container tightly closed. Keep cool.  
 P240 - Ground/bond container and receiving equipment.  
 P241 - Use explosion-proof ventilating, lighting, electrical equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P260 - Do not breathe vapors, mist, spray.  
 P264 - Wash hands, forearms, and exposed areas thoroughly after handling.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P280 - Wear protective clothing, protective gloves, eye protection.

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P301+P310 - IF SWALLOWED: Immediately call POISON CENTER/doctor.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call POISON CENTER/doctor if you feel unwell.  
P321 - Specific treatment (see Section 4).  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P370+P378 - In case of fire: Use water spray, alcohol-resistant foam, carbon dioxide, dry powder to extinguish.  
P403+P405 - Store in a well-ventilated place. Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Other Hazards** Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

**Unknown Acute Toxicity (GHS-US)** Not available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Isopropyl alcohol	(CAS No) 67-63-0	< 55	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS No) 108-88-3	< 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Obtain medical attention if irritation persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause drowsiness and dizziness. Aspiration hazard. Causes irritation. There are potential chronic health effects to consider.

**Inhalation:** Excessive exposure may cause central nervous system effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure, and death.

**Skin Contact:** Causes skin irritation.

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If exposed or concerned, get medical advice and attention.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Flammable liquid and vapor. Vapor is denser than air – flashback may be possible over considerable distances.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### **Advice for Firefighters**

**Firefighting Instructions:** Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus when fighting fire in an enclosed area.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Remove ignition sources. Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not breathe vapor, mist or spray. Use only outdoors or in a well-ventilated area. Handle in accordance with good industrial hygiene and safety practice.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area.

**Environmental Precautions** Prevent entry to sewers and public waters. Contact competent authorities after a spill.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Place absorbed material in a sealed, labelled container for proper disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Handling Temperature:** ≤ 50 °C (122 °F)

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling.

### **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Ground/bond container and receiving equipment.

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Store locked up.

**Incompatible Materials:** Strong oxidizers.

**Specific End Use(s)** Designed to provide an improved retaining grip between the impression tray and any alginate and hydrocolloid impression material.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA IDLH	US IDLH (ppm)	500 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	50 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	60 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	100 ppm
Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA IDLH</b>	US IDLH (ppm)	2000 ppm (10% LEL)
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	984 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	400 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	492 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	200 ppm
<b>British Columbia</b>	OEL STEL (ppm)	400 ppm
<b>British Columbia</b>	OEL TWA (ppm)	200 ppm
<b>Manitoba</b>	OEL STEL (ppm)	400 ppm
<b>Manitoba</b>	OEL TWA (ppm)	200 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	500 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	200 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	400 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	200 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	1228 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	500 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	400 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	1228 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	500 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	400 ppm
<b>Ontario</b>	OEL STEL (ppm)	400 ppm
<b>Ontario</b>	OEL TWA (ppm)	200 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	400 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	200 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	500 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	985 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	400 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	400 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	200 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	500 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	400 ppm

### Exposure Controls

**Appropriate Engineering Controls:** Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapors may be released. Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment:** Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wash contaminated clothing before reuse.

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Viscous, amber colored
Odor	: Characteristic alcohol
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 178 - 181 °F (81.1 - 82. 8 °C)
Flash Point	: 94.1 °F (34.5 °C) Closed Cup
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: 1.3 %
Upper Flammable Limit	: 12 %
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Specific Gravity	: 0.855 - 0.865
Solubility	: In water, material is partially soluble
Partition Coefficient: N-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

**Incompatible Materials:** Strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** Excessive exposure may cause central nervous system effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure, and death.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Symptoms/Injuries After Ingestion:** The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

### Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

<b>Toluene (108-88-3)</b>	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
ATE US (vapors)	25.70 mg/l/4h
<b>Isopropyl alcohol (67-63-0)</b>	
LD50 Oral Rat	4710 mg/kg
LD50 Dermal Rabbit	4059 mg/kg
LC50 Inhalation Rat	72600 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Toluene (108-88-3)</b>	
IARC Group	3
<b>Isopropyl alcohol (67-63-0)</b>	
IARC Group	3

## SECTION 12: ECOLOGICAL INFORMATION

**Toxicity** Not classified

<b>Toluene (108-88-3)</b>	
LC50 Fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)
<b>Isopropyl alcohol (67-63-0)</b>	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodemus subspicatus)
LC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)

**Persistence and Degradability** Not established

### Bioaccumulative Potential

<b>HOLD™ LIQUID TRAY ADHESIVE</b>	
Bioaccumulative Potential	Not established.
<b>Toluene (108-88-3)</b>	
Log Pow	2.65
<b>Isopropyl alcohol (67-63-0)</b>	
Log Pow	0.05 (at 25 °C)

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Avoid release to the environment.

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 14: TRANSPORT INFORMATION

#### In Accordance with DOT

Proper Shipping Name : ADHESIVES containing a flammable liquid  
Hazard Class : 3  
Identification Number : UN1133  
Label Codes : 3  
Packing Group : III  
ERG Number : 127



#### In Accordance with IMDG

Proper Shipping Name : ADHESIVES containing a flammable liquid  
Hazard Class : 3  
Identification Number : UN1133  
Packing Group : III  
Label Codes : 3  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D



#### In Accordance with IATA

Proper Shipping Name : ADHESIVES containing a flammable liquid  
Packing Group : III  
Identification Number : UN1133  
Hazard Class : 3  
Label Codes : 3  
ERG Code (IATA) : 3L



#### In Accordance with TDG

Proper Shipping Name : ADHESIVES containing a flammable liquid  
Packing Group : III  
Hazard Class : 3  
Identification Number : UN1133  
Label Codes : 3



### SECTION 15: REGULATORY INFORMATION

#### US Federal Regulations

<b>HOLD™ LIQUID TRAY ADHESIVE</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
<b>Toluene (108-88-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Isopropyl alcohol (67-63-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 % (only if manufactured by the strong acid process, no supplier notification)

#### US State Regulations

<b>Toluene (108-88-3)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.



# HOLD™ LIQUID TRAY ADHESIVE



## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Toluene (108-88-3)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

<b>Isopropyl alcohol (67-63-0)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

### Canadian Regulations

<b>HOLD™ LIQUID TRAY ADHESIVE</b>	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class B Division 3 - Combustible Liquid
	

<b>Toluene (108-88-3)</b>	
Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

<b>Isopropyl alcohol (67-63-0)</b>	
Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 10/02/2017  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3

# HOLD™ LIQUID TRAY ADHESIVE

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

### Party Responsible for the Preparation of This Document

Water Pik, Inc.

Telephone: 800-525-2020

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*