

Page 1/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 11

Revision: 03.01.2020

Trade name: LubrifluidArricle number: 16000641.2 Relevant identified uses of the substance or mixture and uses advised againstNo further relevant information available.Application of the substance / the mixture:Auxiliary for dental technologyLubricant1.3 Details of the supplier of the safety data sheetManufacturer/Supplier:Bien-Air Dental S.A.Länggasse 60CH-2504 Biel/BienneSwitterlandTel: int. +41 (0)32 344 64 64office@bienair.comFurther information obtainable from: Product safety department1.4 Emergency telephone number:Swits Toxicological information centerE-Mail: info@loxi.ch24-h-Emergency number: From CH: 145 From abroad: +41 44 251 51 51Sectton 2: Hazards identification21.1 Classification of the substance or mixtureClassification according to Regulation (EC) No 1272/2008Section 1H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heateAquatic Chronic 2 H411Toxic to aquatic life with long lasting effects.Skin Irrit. 2Kin Irrit. 2Kin Irrit. 2Kin Irrit. 2H336May cause drowsiness or dizziness.App. Tox. 1H304May be fatal if swallowed and enters airways.	1.1 Product ide	ntifier	
1.3 Relevant identified uses of the substance or mixture and uses advised against         No further relevant information available.         Application of the substance / the mixture:         Auxiliary for dental technology         Lubricant         1.3 Details of the supplier of the safety data sheet         Manufacturer/Supplier:         Bien-Air Dental S.A.         Länggasse 60         CH-2504 Biel/Bienne         Switzerland         Tel: int. +14 (0)32 344 64 64         office@bienair.com         Further information obtainable from: Product safety department         1.4 Emergency telephone number:         Swiss Toxicological information center         E-Mail: info@toxi.ch         24-h-Emergency number: From CH: 145         From abroad: +41 44 251 51 51         SECTION 2: Hazards identification         Classification according to Regulation (EC) No 1272/2008         over         GHS02 flame         Aerosol 1       H22-H229 Extremely flammable aerosol. Pressurised container: May burst if header         Aquatic Chronic 2 H411       Toxic to aquatic life with long lasting effects.         over       GHS09         GHS07       Stin Irrit. 2       H315         Stin Irrit. 2       H336       May cause drowsiness or dizziness.	Trade name: L	ubrifluid	
Manufacturer/Supplier: Bien-Air Dental S.A. Länggasse 60 CH-2504 Biel/Bienne Switzerland Tel.: int. +41 (0)32 344 64 64 office@bienair.comFurther information obtainable from: Product safety department 1.4 Emergency telephone number: Swiss Toxicological information center E-Mail: info@toxi.ch 24-h-Emergency number: From CH: 145 From abroad: +41 44 251 51 51SECTION 2: Hazards identification Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008OutputGHS02 flame Aerosol 1Aerosol 1H222-H229Extremely flammable aerosol. Pressurised container: May burst if heated Output GHS09 environmentAquatic Chronic 2Main Chronic 2Kin Irrit. 2Skin Irrit. 2H315Causes skin irritation. STOT SE 3Stain Irrit. 2H336May cause drowsiness or dizziness.	<b>1.2 Relevant id</b> No further relev <b>Application of a</b> Auxiliary for de	entified uses of pant information the substance /	available. t <b>he mixture:</b>
1.4 Emergency telephone number:         Swiss Toxicological information center         E-Mail: info@toxi.ch         24-h-Emergency number: From CH: 145         From abroad: +41 44 251 51 51         SECTION 2: Hazards identification         21 Classification of the substance or mixture         Classification of the substance or mixture         Classification according to Regulation (EC) No 1272/2008         Image: Classification of the substance or mixture         Classification according to Regulation (EC) No 1272/2008         Image: Classification according to Regulation (EC) No 1272/2008	Manufacturer/A Bien-Air Dentau Länggasse 60 CH-2504 Biel/E Switzerland Tel.: int. +41 (0	<b>Supplier:</b> 1 S.A. Bienne 1)32 344 64 64	ne safety data sheet
2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008         Image: GHS02 flame         Aerosol 1       H222-H229         Extremely flammable aerosol. Pressurised container: May burst if heate         Image: GHS09 environment         Aquatic Chronic 2       H411         Image: Total Chronic 2       H315         Image: Total Chronic 2       H315         Image: Total Chronic 2       H315         Image: Total Chronic 2       H336         Image: Total Chronic 2       H336         Image: Total Chronic 2       H315         Image: Total Chronic 2       H336	1.4 Emergency	telephone num	ber:
Classification according to Regulation (EC) No 1272/2008Image: GHS02 flameAerosol 1H222-H229Extremely flammable aerosol. Pressurised container: May burst if heateImage: GHS09 environmentAquatic Chronic 2H411Toxic to aquatic life with long lasting effects.Image: GHS07Skin Irrit. 2H315Causes skin irritation.STOT SE 3H336May cause drowsiness or dizziness.	E-Mail: info@to 24-h-Emergenc	y number: Fron F	Grom abroad: +41 44 251 51 51
Aerosol 1H222-H229Extremely flammable aerosol. Pressurised container: May burst if heaterImage: Aerosol 1H222-H229Extremely flammable aerosol. Pressurised container: May burst if heaterImage: Aerosol 1GHS09Image: Aerosol 1Image: Aquatic Chronic 2H411Toxic to aquatic life with long lasting effects.Image: Aquatic Chronic 2H411Toxic to aquatic life with long lasting effects.Image: Acrosol 1GHS07Image: Skin Irrit. 2H315Causes skin irritation.Image: Stort SE 3H336May cause drowsiness or dizziness.	E-Mail: info@ta 24-h-Emergenc SECTION 2	y number: Fron F : Hazards i	Grom abroad: +41 44 251 51 51 dentification
Aerosol 1H222-H229Extremely flammable aerosol. Pressurised container: May burst if heaterImage: Aerosol 1H222-H229Extremely flammable aerosol. Pressurised container: May burst if heaterImage: Aerosol 1GHS09Image: Aerosol 1Image: Aquatic Chronic 2H411Toxic to aquatic life with long lasting effects.Image: Aquatic Chronic 2H411Toxic to aquatic life with long lasting effects.Image: Acrosol 1GHS07Image: Skin Irrit. 2H315Causes skin irritation.Image: Stort SE 3H336May cause drowsiness or dizziness.	E-Mail: info@ta 24-h-Emergenc SECTION 2 2.1 Classification	y number: Fron F : Hazards i on of the substa	Trom abroad: +41 44 251 51 51  dentification nce or mixture
Aquatic Chronic 2       H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2       H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2       H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2       H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2       H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2       H411       Causes skin irritation.         Stort SE 3       H336       May cause drowsiness or dizziness.	E-Mail: info@ta 24-h-Emergenc SECTION 2 2.1 Classification Classification a	y number: Fron F <b>: Hazards i</b> on of the substa according to Reg	Trom abroad: +41 44 251 51 51  dentification nce or mixture
Aquatic Chronic 2 H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2 H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2 H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2 H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2 H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2 H411       Toxic to aquatic life with long lasting effects.         Image: Chronic 2 H411       Causes skin irritation.         Stor Image: Chronic 2 H315       Causes skin irritation.         STOT SE 3       H336         May cause drowsiness or dizziness.	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a GHS	y number: From F <b>: Hazards i</b> on of the substa according to Res 02 flame	From abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008
GHS07Skin Irrit. 2H315Causes skin irritation.STOT SE 3H336May cause drowsiness or dizziness.	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a GHS	y number: From F <b>: Hazards i</b> on of the substa according to Res 02 flame	From abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008
<i>GHS07</i> <i>Skin Irrit.</i> 2 <i>H315 Causes skin irritation.</i> <i>STOT SE</i> 3 <i>H336 May cause drowsiness or dizziness.</i>	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a GHSU Aerosol 1	y number: From F <b>: Hazards i</b> on of the substa according to Res 02 flame H222-H229	From abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008
Skin Irrit. 2H315Causes skin irritation.STOT SE 3H336May cause drowsiness or dizziness.	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a Classification a Aerosol 1 Aerosol 1	y number: From F Hazards i on of the substa according to Reg 02 flame H222-H229 09 environment	Trom abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008 Extremely flammable aerosol. Pressurised container: May burst if heate
STOT SE 3 H336 May cause drowsiness or dizziness.	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a Classification a Aerosol 1 Aerosol 1	y number: From F Hazards i on of the substa according to Reg 02 flame H222-H229 09 environment	Trom abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008 Extremely flammable aerosol. Pressurised container: May burst if heate
STOT SE 3 H336 May cause drowsiness or dizziness.	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a GHSt Aerosol 1 Aquatic Chroni	y number: From F Hazards i on of the substa according to Reg 02 flame H222-H229 09 environment c 2 H411	Trom abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008 Extremely flammable aerosol. Pressurised container: May burst if heate
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	E-Mail: info@ti 24-h-Emergenc SECTION 2 2.1 Classification Classification a GHSU Aerosol 1 Aquatic Chronii Aquatic Chronii	y number: From F <b>: Hazards i</b> on of the substa according to Res 02 flame H222-H229 09 environment c 2 H411 07	Trom abroad: +41 44 251 51 51         dentification         nce or mixture         gulation (EC) No 1272/2008         P Extremely flammable aerosol. Pressurised container: May burst if heate         Toxic to aquatic life with long lasting effects.
	E-Mail: info@ti 24-h-Emergenc SECTION 2 24-h-Emergenc SECTION 2 2 24-h-Emergenc 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	y number: From F Hazards i on of the substa according to Res 02 flame H222-H229 09 environment c 2 H411 07 H315	Trom abroad: +41 44 251 51 51 dentification nce or mixture gulation (EC) No 1272/2008 Extremely flammable aerosol. Pressurised container: May burst if heate Toxic to aquatic life with long lasting effects. Causes skin irritation.

Version number 11

Revision: 03.01.2020

Printing date 03.01.2020
Trade name: Lubrifluid

· Hazard J	pictograms (Contd. of page
<b>(</b> (1))	
	$\vee$ $\vee$
GHS02	GHS07 GHS09
· Signal w	vord Danger
· Hazard-	determining components of labelling:
	rbons, C6, isoalkanes, <5% n-hexane
Hydroca	rbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane
Hydroca	rbons, C7-C9, n-alkanes, isoalkanes, cyclics
1-Decen	, Dimer, hydriert
· Hazard s	statements
Н222-Н2	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
	onary statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P273	Avoid release to the environment.
P280	Wear protective gloves.
	352 IF ON SKIN: Wash with plenty of water.
P304+P.	340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
	313 If skin irritation occurs: Get medical advice/attention.
	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
· Addition	al information:
	of explosive mixtures possible without sufficient ventilation.
· 2.3 Othe	
· Results (	of PBT and vPvB assessment
· PBT: No	ot applicable.
	ot applicable.
SECTI	ON 3: Composition/information on ingredients

· Description: Active substance with propellant

CAS: 75-28-5	isobutane	20-30%
EINECS: 200-857-2	🚸 Flam. Gas 1, H220; Press. Gas C, H280	-
Index number: 601-004-00-0		
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 74-98-6	propane	10-20%
EINECS: 200-827-9	🚸 Flam. Gas 1, H220	-
Index number: 601-003-00-5		
Reg.nr.: 01-2119486944-21-xxxx		
EC number: 931-254-9	Hydrocarbons, C6, isoalkanes, <5% n-hexane	10-20%
Index number: 649-328-00-1	🚸 Flam. Liq. 2, H225; 🚯 Asp. Tox. 1, H304; 🚯 Aquatic	-
Reg.nr.: 01-2119484651-34-xxxx	Chronic 2, H411; 🚯 Skin Irrit. 2, H315; STOT SE 3, H336	

Printing date 03.01.2020

Version number 11

Revision: 03.01.2020

Trade name: Lubrifluid

EC 1 021 024 (		d. of page 2
<i>EC number: 921-024-6</i>	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-	10-20%
Reg.nr.: 01-2119475514-35	hexane	
	🚸 Flam. Liq. 2, H225; 🚯 Asp. Tox. 1, H304; 🚯 Aquatic	
	Chronic 2, H411; 🚯 Skin Irrit. 2, H315; STOT SE 3, H336	
EC number: 927-510-4	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	10-20%
Reg.nr.: 01-2119484651-33	🕐 Flam. Liq. 2, H225; 🚸 Asp. Tox. 1, H304; 🔖 Aquatic	
	Chronic 2, H411; 🚯 Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 124-38-9	carbon dioxide	1-10%
EINECS: 204-696-9	substance with a Community workplace exposure limit	
CAS: 68649-11-6	1-Decen, Dimer, hydriert	1-10%
	<b>♦</b> <i>Asp. Tox. 1, H304;</i> <b>♦</b> <i>Acute Tox. 4, H332</i>	1

Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

<sup>-</sup> EU

Printing date 03.01.2020

Version number 11

Revision: 03.01.2020

(Contd. of page 3)

#### Trade name: Lubrifluid

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions:
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

124-38-9 carbon dioxide

*IOELV* Long-term value: 9000 mg/m<sup>3</sup>, 5000 ppm

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### Respiratory protection:

Use suitable respiratory protective device when high concentrations are present. Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Not necessary if room is well-ventilated.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.3$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

EU

Version number 11

Revision: 03.01.2020

Trade name: Lubrifluid

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Not required.

SECTION 9: Physical and ch	
9.1 Information on basic physical and c	chemical properties
General Information	
Appearance: Form:	1
Form: Colour:	Aerosol Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: Not applicable, as aerosol.
Flash point:	-60 °C
Flammability (solid, gas):	Extremely flammable liquefied gas.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	10.9 Vol %
Vapour pressure:	Not determined.
Density at 20 °C:	$0.62 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	82.5 %
VÕC (EC)	82.55 %
9.2 Other information	No further relevant information available.

# **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

(Contd. on page 6) EU

(Contd. of page 4)

Printing date 03.01.2020

Version number 11

Revision: 03.01.2020

(Contd. of page 5)

Trade name: Lubrifluid

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

- No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions Reacts violently with oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

## **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 04 metallic packaging

(Contd. on page 7)

nting date 03.01.2020 Vers.	ion number 11 Revision: 03.01.2
ide name: Lubrifluid	
	(Contd. of page
15 01 10* packaging containing residues of or	contaminated by hazardous substances
• Uncleaned packaging: • Recommendation: Disposal must be made acco	rding to official regulations.
SECTION 14: Transport information	on
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkan cyclics, < 5% n-hexane, Hydrocarbons, C7-C9, n-alkan isoalkanes, cyclics), MARINE POLLUTANT
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	2 5F Gases. 2.1
· IMDG	2.1
· Class · Label	2.1 2.1
	2,1
· IATA	2.1
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substance oleoylsarcosine
· Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> </ul>	Warning: Gases. -
· EMS Number:	F-D,S-U

(Contd. on page 8) EU

Printing date 03.01.2020	Version number 11	Revision: 03.01.2020
Trade name: Lubrifluid		
		(Contd. of page 7)
• Stowage Code • Segregation Code	Category A. For AEROSO Category B. For WASTE of living quarters. SG69 For AEROSOLS wi Segregation as for class except for division 1.4. For AEROSOLS with a ca Segregation as for the app For WASTE AEROSOLS:	ith a maximum capacity of 1 litre: DLS with a capacity above 1 litre: AEROSOLS: Category C, Clear th a maximum capacity of 1 litre: 9. Stow "separated from" class 1 apacity above 1 litre: propriate subdivision of class 2.
• 14.7 Transport in bulk according		
Marpol and the IBC Code	Not applicable.	
• Transport/Additional information • ADR		
· ADK · Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted	d Ouantity
• Transport category • Tunnel restriction code	2 D	~ `
· IMDG		

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY · UN "Model Regulation": HAZARDOUS

lL

Code: E0

Not permitted as Excepted Quantity

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

Limited quantities (LQ) • Excepted quantities (EQ)

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.

> (Contd. on page 9) EU

Printing date 03.01.2020

Version number 11

Revision: 03.01.2020

# Trade name: Lubrifluid

(Contd. of page 8)
H411 Toxic to aquatic life with long lasting effects.
• Department issuing SDS: Product Stewardship
Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity - inhalation – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
* Data compared to the previous version altered.
EU