

# SAFETY DATA SHEET SDS No. 845

Revision Date: September 23, 2020 Version: 9.0

**☑** GHS Compliant

# Section 1 - Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Trade Name: SuperSeal

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Release agent Restrictions on Use: None known

1.3 Details of the supplier of the safety data sheet:

Company: Smooth-On, Inc.,

5600 Lower Macungie Rd., Macungie, PA 18062

Telephone: Phone (610) 252-5800 FAX (610) 252-6200

E-mail address: Visit our website at www.smooth-on.com or email

www.sds@smooth-on.com

1.4 Emergency Contact: Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

# Section 2 – Hazard(s) Identification

## 2.1 Classification of the substance or mixture:

GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

**H225** Flammable liquid – Category 2

H304 Aspiration Hazard - Category 1

H315 Skin Irritation - Category 2

**H336** Specific target organ toxicity-single exposure – Category 3 (central nervous system)

# 2.2 GHS Label elements, including precautionary statements



> 😵

Pictogram(s):

Signal word: Danger

Physical Hazards

H225 Highly flammable liquid and vapor

**Health Hazards** 

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

**General Precautions** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

<b>Prevention Statements</b>	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response Statements	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
F303 + F301 + F333	clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for
1 304 1 1 340	breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use Water Fog, Dry Chemical, and Carbon Dioxide
	Foam to extinguish.
P391	Collect spillage.
Storage Statements	
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal Statements	
P501	Dispose of contents/container according to local, state and federal laws.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – none known

# **Section 3 - Composition / Information on Ingredients**

# 3.1 Substances/Mixtures

The following ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR 1910.1200:

Chemical name	CAS-No.	Concentration
Naphtha (Petroleum), Light Alkylate	64741-66-8	70% - 80%
2-propanol	67-63-0	<15%

## Section 4 - First Aid Measures

## 4.1 Description of first aid measures

## Inhalation

Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

## **Eye Contact**

Flush eyes with plenty of water occasionally lifting the upper and lower eyelids. Check and remove any contact lenses if safe to do so. Continue to rinse for at least 15 minutes. If irritation develops, seek medical attention.

## **Skin Contact**

In case of skin contact, wash thoroughly with soap and water. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician.

# Ingestion

Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. if vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

# 4.2 Most important symptoms and effects, both acute and delayed

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

4.3 Indication of any immediate medical attention and specific treatment needed, if necessary.

## **Section 5 - Fire-Fighting Measures**

# 5.1 Extinguishing Media

Water Fog, Dry Chemical, and Carbon Dioxide Foam

## 5.2 Special hazards arising from the substance or mixture

In a fire or if heated, a pressure increase will occur, and the container may burst.

## 5.3 Advice for firefighters

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure demand or positive-pressure mode.

## **Section 6 - Accidental Release Measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.

## 6.2 Environmental precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.

## 6.3 Methods and material for containment and cleaning up

Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.

## 6.4 Reference to other sections

See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

# Section 7 - Handling and Storage

# 7.1 Precautions for safe handling

Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet local standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

## 7.3 Specific end use(s)

These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

## Section 8 - Exposure Controls / Personal Protection

## 8.1 Control parameters

## Components with workplace control parameters

Basis	Value	Parameter	
ACGIH Threshold Limit Values	TWA	300 ppm	
OSHA Table Z-1	TWA	2,350 ppm (5,758 mg/m3)	
2-propanol (vapor)			
Basis	Value	Parameter	
ACGIH Threshold Limit Values	TWA	200 ppm	
	STEL	400 ppm	
OSHA Table Z-1	TWA	400 ppm (980 mg/m <sup>3</sup> )	
NIOSH	TWA	400 ppm (980 mg/m <sup>3</sup> )	
	ST	500 ppm (1,225 mg/m <sup>3</sup> )	

# 8.2 Exposure controls

## **Respiratory Protection**

Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

#### **Hand Protection**

Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

## **Eye Protection**

Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

## **Other Protective Clothing/Equipment**

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

## **Comments**

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

# **Section 9 - Physical and Chemical Properties**

## 9.1 Information on basic physical and chemical properties

Appearance:	liquid	Vapor pressure:	~63 mmHg @ 68 °F
Odor:	Mild petroleum/solvent	Vapor density (Air=1):	~4
pH:	9.0 - 9.5	Auto-ignition temperature:	750 °F (approx.)
Flash Point:	>19 °F	Solubility in water:	Insoluble
		Specific Gravity	
Melting / freezing point:	No data	(H2O=1, at 4 °C):	0.72
Low / high boiling point:	205 °F/255 °F	Relative density:	No data
Upper flammability limits:	No data	% Volatile:	80%-85% (612 g/l)
Lower flammability limits:	11.6%(V)/1.5%(V)	Viscosity:	20,000 – 30,000
			centipoise

# Section 10 - Stability and Reactivity

## 10.1 Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.

## 10.2 Chemical stability

These products are stable at room temperature in closed containers under normal storage and handling conditions.

# 10.3 Possibility of hazardous reactions

Hazardous polymerization cannot occur

## 10.4 Conditions to avoid

None known

## 10.5 Incompatible materials

Strong bases and acids

## 10.6 Hazardous decomposition products

Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

# **Section 11- Toxicological Information**

## 11.1 Information on toxicological effects

# **Acute Toxicity**

No data available

## **Skin Corrosion/Irritation**

No data available

# Serious Eye Damage/Irritation

No data available

## **Respiratory/Skin Sensitization**

No data available

## Germ Cell Mutagenicity

No data available

## Carcinogenicity

No component of these products present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC, ACGIH or NTP.

# **Reproductive Toxicity**

No data available

# Specific Target Organ Toxicity - Single Exposure

No data available

## **Specific Target Organ Toxicity – Repeated Exposure**

No data available

# **Aspiration Hazard**

No data available

## Potential Health Effects - Miscellaneous

No data available

# **Section 12 - Ecological Information**

# 12.1 Toxicity

No data available

# 12.2 Persistence and Degradability

No data available

## 12.3 Bioaccumulative Potential

No data available

## 12.4 Mobility in Soil

No data available

#### 12.5 Results of PBT and vPvB assessment

No data available

## 12.6 Other Adverse Effects

No data available

# **Section 13 - Disposal Considerations**

#### 13.1 Waste treatment methods

Under Resource Conservation and Recovery Act (RCRA) it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste as defined in 40 CFR Part 261. Waste management should be in full compliance with federal, state and local laws. Regulations may vary in various locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

# **Container disposal**

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

# **Section 14 - Transport Information**

# Regulated by DOT / IMDG / IATA

	Land transport (DOT)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number:	UN 1866	UN 1866	UN 1866
UN proper shipping name:	Resin solution	Resin solution	Resin solution
Transport hazard class(s):	3	3	3
Packing group:	II	II	II
Environmental hazards:	N/A	N/A	N/A
Special precautions for user:	-	-	-
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	-	-	-

# **Section 15 - Regulatory Information**

# 15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016)

This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

# In the United States (EPA Regulations) TSCA Inventory Status (40 CFR710)

All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

## **CERCLA Hazardous Substance List (40 CFR 302.4)**

None known.

## **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and community Right-to-Know Act of 1986) Sections 311 and 312

Fire. Immediate health.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# State Right-to-Know

Component CAS# State

Naphtha (Petroleum), Light Alkylate 64741-66-8 IL, LA, MI 293, MN, NJ, PA, RI

## **California Proposition 65**

This product does not intentionally contain any chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

## 15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this substance/mixture by the supplier.

# 16 - Other Information





Revision Date: September 23, 2020 Version: 9.0

## Abbreviations and acronyms

ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard

Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

## **Disclaimer**

The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.