Material Safety Data Sheet

Issued: 02/26/2013 Revision Number: 14

Identification of Substance /Preparation and Company /Undertaking

Product Name: ALL-ETCH/ UNI-ETCH/SELECT HV ETCH/ETCH-37 (with/without BAC)
Manufacturer: Bisco, Inc. 1100 W Irving Park Road, Schaumburg, IL 60193 USA

Telephone: 1-847-534-6000, during normal business hours

Emergency CHEMTREC - 24-Hour Hazmat Emergency Communications Center

Telephone Number: Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

EC Representative: Bisico France, 120, allée de la Coudoulette, 13680 Lançon de Provence, France

Telephone: 33-4-90-42-92-92

2.	Composition/Information on Ingredients			_			
	Ingredient	Concentration	CAS Number	Symbol/Risk	OSHA PEL	ACGIH	LD50
		Range		Classificaton	(mg/m3)	(mg/m3)	(mg/kg,
		(%)					rat/oral)
	ALL-ETCH: Phosphoric Acid.	>10.	7664-38-2.	Xi; R36/38.	1.	1.	1530.
	UNI-ETCH: Phosphoric Acid.	>25.	7664-38-2.	C; R34.	1.	1.	1530.
	ETCH-37: Phosphoric Acid	>25	7664-38-2	C; R34	1	1	1530
	SELECT HV ETCH-; Phosphoric Acid.	>25	7664-38-2	C; R34	1	1	1530
	Benzalkonium Chloride (BAC)*. * only for those marked with BAC	1.	8001-54-5.	Xi; R36/38.	N/D.	N/D.	240.

3. Hazards Identification

Irritant; Irritating to eyes and skin, Corrosive; Causes burns.

4. First-aid Measures

Inhalation: Provide fresh air and rest. Get medical attention.

Skin Contact: Wash with soap and water.

Eye Contact: Flush with running water for at least 15 minutes while keeping eye lids open; seek medical attention.

Ingestion: Drink two glasses of water or milk. Seek medical attention if a substantial amount has been ingested. Do

not induce vomiting.

5. Fire-fighting Measures

Fire-fighting media: Dry chemical powder, foam or carbon dioxide.

Fire and explosion risks: Upon combustion, irritating gases may form.

6. Accidental Release Measures

Personal Precautions: Prevent skin/eye contact.

Environmental Precautions: Avoid ground water contamination.

Methods for Cleaning Up: Wipe with damp paper towels, Discard properly.

7. Handling and Storage

This product is used exclusively for dental purposes by trained personnel, Use according to directions for use. Store at room temperature (20°C/68°F - 25°C/77°F) in the original container provided by the manufacturer. Avoid skin contact. At high temperatures toxic fumes of phosphoric acid and phosphorous oxides can be generated. Advoid or protect from sunlight.

8. Exposure Controls / Personal Protection

Eye Protection: Use protective eyewear.

Hand Protection: Use protective gloves.

Respiratory Protection: Avoid prolonged breathing of vapors of uncured material.

Skin Protection: Use any necessary hygiene measures.

9.	Phy	vsical	1	Chemical	F	roi	perties
----	-----	--------	---	----------	---	-----	---------

Semi-gel	Vapor Pressure @ 20C/68F	N/A
Blue or Green	Miscibility	N/A
Odorless	Vapor Density	N/A
Miscible	pН	<1
>100°C / 212°F	Evaporation Rate	N/A
< 0°C / 32°F	Viscosity	N/A
N/A	Partition Coefficient	N/A
N/A	Autoflammability	N/A
N/A	Flammability	N/A
N/A	Relative Density	N/A
	Blue or Green Odorless Miscible >100°C / 212°F < 0°C / 32°F N/A N/A N/A	Blue or Green Miscibility Odorless Vapor Density Miscible pH >100°C / 212°F Evaporation Rate < 0°C / 32°F Viscosity N/A Partition Coefficient N/A Autoflammability N/A Flammability

10. Stability and Reactivity

Stable. Avoid high temperatures. Incompatible with strong caustics, metals, sulfides, and sulfites.

11. Toxicological Information

Eve Contact: Causes burns...

Skin Contact: Causes burns...

Sensitization: May cause allergic reaction on contact with the skin.

Other: If swallowed, may cause sore throat and burns of the mouth and throat. Prolonged

exposure may cause burns to the respiratory tract, contact with soft tissue may cause

burns..

12. Ecological Information

There is no specific information on the product. Use according to good working practices, avoiding release of the product into environment.

13. Disposal Considerations

Refer to any Community provisions relating to waste. In their absence, refer to National or Regional provisions relating to waste.

14. Transport Information

DOT Regulations:

Hazard Člass: 8

Identification Number: UN 1805

Packing Group: III

Proper Shipping Name: Phosphoric Acid, with not more than 85 percent strength

Land Transport ADR/RID (cross-border):

Hazard Class: 8

Identification Number: UN 1805

Packing Group: III

Proper Shipping Name: Phosphoric Acid, with not more than 85 percent strength

Maritime Transport IMDG:

Hazard Class: 8

Identification Number: UN 1805

Packing Group: III

Proper Shipping Name: Phosphoric Acid, with not more than 85 percent strength

Air Transport ICAO-TI and IATA-DGR:

Hazard Class: 8

Identification Number: UN 1805

Packing Group: III

Proper Shipping Name: Phosphoric Acid, with not more than 85 percent strength

15. Regulatory Information

Classification: Xi Irritant, C Corrosive, R34 Causes burns., R36 Irritating to eyes., R38 Irritating to skin.

Safety: S1/2 Keep locked up and out of the reach of children. S26 In case of contact with eyes rinse

immediately with water and seek medical advice. S45 In case of accident or if you feel unwell

seek medical advice immediately (show label where possible)...

Other Information

Revision Date: 02/26/2013

Replaces MSDS dated: 06/12/2012 Product: ALL-ETCH/ UNI-ETCH/SELECT HV ETCH/ETCH-37 Revision Number: 14

(with/without BAC)

This information is believed to be correct as of the date of this MSDS. The manufacturer makes no representation as to the completeness or accuracy of this information and supplies it on the condition that the person receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

NOTE: CHEMTREC provides an emergency telephone number in the event of an emergency for leak, fire, exposure or accident involving the hazardous material that is being shipped. All non-emergency inquiries should be directed to Bisco during normal working hours.