Date of issue: June 2004 Supersedes version of: January 2003 Page 1 of 2 n.a. = not applicable, n.k = not known P/N 48078A

1. Identification of the substance / preparation and of the company / undertakings

Product Details:

Trade Name: Red Utility Wax

Manufacturer:

Coltène/Whaledent Inc. 235 Ascot Parkway Cuyahoga Falls, OH 44223 / USA

Cuyahoga Falls, OH 44223 / US. Fax +1 330 916 7077 info@coltenewhaledent.com

Emergency Contact Numbers: USA & Canada: 1 800 535 5053 Main Phone Number: +1 330 916 8800 Authorized EU Representative Coltène/Whaledent GmbH+ Co. KG

Raiffeisenstrasse 30 89129 Langenau / Germany Tel. +49 (0) 7345 805 0 Fax +49 (0) 7345 805 201

 Composition / information on ingredients Chemical characterization: Dental Wax

Hazardous components: WT % R & S Phrases

None

Non-hazardous components (>10%)
Petroleum Hydrocarbons & Additives

Petroleum Hydrocarbons & Additives >50% n.a.

3. Hazard identification

Hazard Designation: Non-Hazardous at room temperature. Above its melting point, wax becomes a liquid and flows more readily as its temperature increases. If material is used as a hot liquid, it requires special handling. At temperatures significantly above its melting point, hydrocarbon vapors are given off which should be handled with adequate ventilation. Can cause eye, skin and respiratory irritation when heated significantly above its melting point.

Information pertaining to particular dangers for man and environment: None Classification is in line with BC directive 88/379/EEC: Not Applicable (N/A)

4. First-aid measures

General Information: Not a hazardous material at room temperature. If exposed to melted wax, see below. After inhalation: Remove individual to a well-ventilated area for fresh air, and call a physician if symptoms

persist.

After skin contact: Exposure to fumes vapor and smoke from thermal degradation can cause irritation.

Exposure to molten material can cause burns. Run exposed area under water for 15 minutes, then contact a physician. Do not attempt to remove material bonded to skin. Exposure to fumes vapor and smoke from thermal degradation can cause irritation. Direct

After eye contact: Exposure to fumes vapor and smoke from thermal degradation can cause irritation. Dire contact with molten material will cause eye injury. Flush eyes with copious amounts of

water for 15 minutes, administer first aid, and call a physician.

After swallowing: Material is not generally toxic by ingestion.

5. Fire-fighting measures

Flammability: Non-Flammable Flash Point: n.a. LEL: n.a. UEL: n.a Extinguishing media: Carbon dioxide, Foam and dry chemicals

Unsuitable extinguishing media: Do not use direct water stream.

Protective Equipment: n.a.

6. Accidental release measures

Personal precautions: No smoking.
Environmental precautions: Observe local by-laws

Method for clean up: Handle as a thermoplastic. Allow molten material to cool and solidify before handling.

7. Handling and storage

Handling: Use appropriate PPE when handling molten wax. Storage: Store in a dry place, away from heat and flames.

8. Exposure controls/ personal protection

Components with recommended limits for the work place

CAS No. Description Wt% Type / Value

None

General: None needed if used at room temperature. If used in a molten state, wear appropriate PPE (thermal gloves, safety glasses and an apron or appropriate splash guard. If used molten, ensure adequate ventilation.

Material Safety Data Sheet in Accordance with 91/155/EEC & ANSI 400.1.2003

Date of Issue: June 2004 Supersedes version of: January 2003 Page 2 of 2 n.a = not applicable, n.k. = not known Red Utility Wax P/N 48078A

9. Physical and chemical properties

Appearance

Form: Rods or Square Ropes Color: Red Odor: Mild

Information on change in physical state:

Boiling point/boiling range (°C) > 316

Melting point/ range (°C) 56-60

Flashpoint (°C) 220

PH n.a.

Ignition temperature n.k.

Explosion hazard n.k.

Explosive limits (Vol%) LEL n.k.

Other information

Relative density 1.0 g/ml Vapor pressure < 0.5 mmHg

Viscosity n.k.

10. Stability and reactivity

If stored and handled in accordance with manufacturers instructions for use no hazardous reactions are known. Avoid strong oxidizing agents like peroxides and chlorines. Will decompose into Carbon dioxide, monoxide, and other ketones and aldehydes when heated well above its boiling point.

11. Toxicological information

Not expected to be a health hazard

12. Ecological information

Material is not considered harmful to the environment.

13. Disposal considerations

Not a RCRA hazardous waste material. Small quantities may be disposed of in a domestic waste.

14. Transportation information

DOT Shipping Name: DOT Hazard Class: UN-No. Non-Regulated Non-Regulated N.A.

UN. No.: N.A.

Sea Transport IMDG/GGV Sea

Class: N.A.

Air Transport ICAO-Ti and IATA-DGR

Class: N.A. UN. No.: N.A.

15. Regulatory information

TSCA Inventory Status: This product and/or all of its components are included on the TSCA Inventory of Chemical Substances.

EmS-No: N.A.

MFGA-No: N.A.

SARA 311/312 Hazard Categories: None

SARA 302 Extremely Hazardous Substances: None

SARA 313 Toxic Chemicals: None

Labeled in accordance with EC directives

Canadian Regulations: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Product Regulations.

16. Other information

06-15-04 – Converted to new format.

The information and recommendations set forth herein are presented in good faith and are believed to be correct as of the date hereof. Coltène/Whaledent Inc., however, makes no representations as to the completeness of security of this information and supplies it on the condition that the persons receiving same will make their own determination as to its suitability of their purposes prior to use. In no event will Coltène/Whaledent Inc. be responsible for damages of any nature whatsoever resulting from use of or reliance upon information.